

**Information to the Company**

Name of Company: <i>(alternative: company's stamp)</i>		Date: <i>(dd/mm/yy)</i>
Responsible Person at the company:		Agent Code: <i>(internal use only)</i>
Address:		Customer No.: <i>(if available)</i>
Post code/city/country:		
Phone / Mobile:		
Email Address:		
Offer required until: <i>(dd/mm/yy)</i>		Delivery required until: <i>(dd/mm/yy)</i>
Quantity pumps required for this application:		Subject / Commission:
Industry: <input type="checkbox"/> Agriculture <input type="checkbox"/> Anaerobic Digestion <input type="checkbox"/> Environmental <input type="checkbox"/> Food & Beverage <input type="checkbox"/> Oil & Gas <input type="checkbox"/> Shipbuilding & Marine <input type="checkbox"/> Chemical Industry / Paper Processing <input type="checkbox"/> Pharmaceuticals + Cosmetics <input type="checkbox"/> Waste Water System		

Information to the Medium**Medium Name:**Flowability similar to *(e.g. Honey, Butter, yogurt, ...)*:

Solids content % TS:	<input type="checkbox"/> abrasive	<input type="checkbox"/> chem. aggressive
Solids size [mm]:	<input type="checkbox"/> hard	<input type="checkbox"/> round <input type="checkbox"/> soft <input type="checkbox"/> stringy <input type="checkbox"/> sharp cornered
Viscosity [mPa·s]:	Temperature [°C]:	
Specific gravity: [kp/dm³]:	pH:	
Flow rate:	Information in <input type="checkbox"/> [l/h] <input type="checkbox"/> [l/Min] <input type="checkbox"/> [m³/h]	

Additional Information *(e.g. Ingredients)*:**Information to the Suction side**

Pressure: <input type="checkbox"/> positive <input type="checkbox"/> negative	How high?:	Information in <input type="checkbox"/> [bar] <input type="checkbox"/> [mWc]
Suction/inflow pipe length [m]:	Diameter Ø [mm]:	
Additional Information: <input type="checkbox"/> elbow: pcs	<input type="checkbox"/> T-piece: pcs	<input type="checkbox"/> flat slide valve: pcs

Information to the Discharge side:

Pressure:	Information in <input type="checkbox"/> [bar] <input type="checkbox"/> [mWc]
Discharge pipe length [m]:	Diameter Ø [mm]:
Additional Information: <input type="checkbox"/> elbow: pcs	<input type="checkbox"/> T-piece: pcs <input type="checkbox"/> flat slide valve: pcs

Pump design and specific Materials

Pump Design:	<input type="checkbox"/> Standard (horizontal)			
	<input type="checkbox"/> Hopper Pump		Hopper size [L x W] [mm]:	
	<input type="checkbox"/> Immersion (vertical)		Immersion depth: [mm]:	
	<input type="checkbox"/> Floor cage		<input type="checkbox"/> Mounting bracket	<input type="checkbox"/> homogeniser
	<input type="checkbox"/> Fugator		<input type="checkbox"/> Rotomix	<input type="checkbox"/> Flange
Operation time [h/day]:		Turn-on frequency per day:		
Housing:	<input type="checkbox"/> cast iron	<input type="checkbox"/> steel	<input type="checkbox"/> 1.4301	<input type="checkbox"/> 1.4571
Rotating parts:			<input type="checkbox"/> 1.4301	<input type="checkbox"/> 1.4571
Rotor:	<input type="checkbox"/> hollow (nitrided)			
	<input type="checkbox"/> full	<input type="checkbox"/> 1.2436H	<input type="checkbox"/> ST-H	<input type="checkbox"/> 1.4301 <input type="checkbox"/> 1.4571
Stator:	<input type="checkbox"/> NBR	<input type="checkbox"/> EPDM	<input type="checkbox"/> FPM	<input type="checkbox"/> other <input type="checkbox"/> Dry-running protection
Universal joint:	<input type="checkbox"/> with sleeve		<input type="checkbox"/> with feed screw	
Shaft sealing:				
Suction flange:	DN	<input type="checkbox"/> PN16	<input type="checkbox"/> DIN11851	Others:
Discharge flange:	DN	<input type="checkbox"/> PN16	<input type="checkbox"/> DIN11851	Others:

Planned pump:

(internal use only)

Which type of pump currently in use:

How many:

Additional Information:

Cleaning in Place

Cleaning in Place CIP: ☐ yes ☐ no Max. Temperature [°C]:

Medium: (Concentration in %)

Motor

<input type="checkbox"/> gear motor		
<input type="checkbox"/> Power Take-Off (PTO)	Size [mm]:	
<input type="checkbox"/> Hydraulic Motor		
<input type="checkbox"/> direct to electricity supply	<input type="checkbox"/> has frequency converter	<input type="checkbox"/> offer with frequency converter
Rating [kw]:		Protection Class: IP
Voltage:	<input type="checkbox"/> multi range / Standard	<input type="checkbox"/> other Voltage:
Frequency:	<input type="checkbox"/> 50 Hz	<input type="checkbox"/> 60 Hz
Additional Information:		

Installation

☐ base frame ☐ base bracket ☐ mobile

Lack Coating

Location:	<input type="checkbox"/> outdoor	<input type="checkbox"/> indoor	
Lack Coating:	<input type="checkbox"/> Standard (C1)	<input type="checkbox"/> neutral (C2 / C3)	<input type="checkbox"/> aggressive (C4 / C5)
	<input type="checkbox"/> special colour:		

Certificates

☐ DIN EN 10204, 3.1 ☐ ATEX (add. Questionnaire to be completed) ☐ EHEDG ☐ 3A

Other Important information